

USB-Serial-Cable-F



USB TO SERIAL CABLE (FEMALE)

Price **5.95 EUR**

10 - 49 pcs **5.36 EUR**

50 - 10000 pcs **4.76 EUR**

[Add to basket](#)

Completely assembled and tested USB serial cable with female connectors. Suitable for OLinuXino and SOM boards among others.

FEATURES

USB to serial cable

Three wires for Breadboard connection

SERIAL output 3.3V voltage levels

GND=BLUE, RX(INPUT)=GREEN,

TX(OUTPUT)=RED

SOFTWARE

[USB-SERIAL-CABLE drivers](#)

FAQ

How do I connect the cable to the RX and TX signals of my target board?

The RX line of the cable (GREEN wire) should go to TX line of the target board; the TX line of the cable (RED wire) should go to the RX line of the target board. The BLUE wire should go to the target's GND line.

What are the serial port settings?

After you install the drivers the default terminal settings for the port associated with USB-SERIAL-CABLE-F are: 115200 baud, 8-N-1

Related Products



MOD-USB-RS232

Price **10.95 EUR**

10 - 49 pcs **9.86 EUR**

50 - 10000 pcs **8.76 EUR**

[Add to basket](#)


USB-Serial-Cable-M

Price **5.95 EUR**

10 - 49 pcs **5.36 EUR**

50 - 10000 pcs **4.76 EUR**

[Add to basket](#)

